



MATERIAL LIST:

- ①PIN:DB9F
- ②BOLT:4*37 BLACK 2PCS
- ③RUBBER:45P PVC BLACK 31.35g
45P PVC BLACK Rebuild-material 9.8g
- ④CABLE:
1)UL2464 26AWG*6C+AEB OD=5.0 BLACK
2)UL2464 26AWG*4C+AEB OD=5.0 BLACK
CORE CABLE:BLACK, GREEN, RED, WHITE
3)UL2464#26*6C+AEB OD=5.0 BLACK
CORE CABLE:BLACK, BROWN, RED, ORANGE, YELLOW, GREEN
- ⑤Hot-shrink JACKET:φ5.0*25 BLACK THIN UL TYPE
- ⑥END: Tie-in PH Pitch:2.0mm PH-T
- ⑦HOUSING:PH Pitch:2.0mm 5P WHITE PH-5Y
- ⑧PIN:MD 6pin M BLACK
- ⑨PIN:MD 6pin F BLACK
- ⑩OT END: (60440-BS-2) ∅4.0mm
Hot-shrink JACKET:φ3.0*15 BLACK THIN UL TYPE
CABLE:UL 1007 22AWG BLACK L=510MM
Hot-shrink JACKET:φ1.0*26 BLACK THIN UL TYPE
φ2.5*8 BLACK THIN UL TYPE

PIN ASSEMBLY:

MD6F	MD6M	DB9F	YELLOW	PH-5P
1 — YELLOW	1	2 —	YELLOW	2
2 — BROWN	2	3 —	ORANGE	3
3 — BLACK	3	5 —	BLACK	5
4 — RED	4	1+6 —	RED	5
5 — ORANGE	5	8 —	GREEN	1
6 — GREEN	6		GND+KNIT	
Outer Shell — GND+KNIT	Outer Shell —	Outer Shell —		

4(amalgamate)
OT END ∅4.0

<p>DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS TOLERANCES ARE: LINEAR TOL: .XX±0.5 ANGULAR TOL: ±1°</p>						MODEL 14-111-180	PROJECTION 	
						DESCRIPTION 232 standard cable	SIZE: A4 SCALE 1:1	
						MATERIAL	WEIGHT: Kg	
						FINISH	COLOR: BLACK	
A	FIRST ISSUE	07-1-12	Sara	Kevin	Gray Wang	DRAWING NO.:	SHEET 1 OF 1	REV. A
REV.	DESCRIPTION	DATE	DRAW	CHECK	APPROVE			