



CONNECTION CHART			
PIN	SIGNAL	INSULATION COLOR	JACKET COLOR
1	GROUND	OVERALL SHIELD	
2	KEY		
3	Y RECEIVE+	BLU	BLK
4	Y TRANSMIT+	BLU	GRY
5	Y RECEIVE-	BLK	BLK
6	Y TRANSMIT-	YEL	GRY
7	GROUND	INNER SHIELD	
8	X TRANSMIT-	RED	RED
9	X RECEIVE-	RED	BLK
10	X TRANSMIT+	GRN	RED
11	X RECEIVE+	WHT	BLK
12	KEY		

- NOTES:
1. ALL DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS SHOWN ARE PROJECTED DISTANCES.
 2. WATERPROOF, DUSTPROOF, ANTIMAGNETIC, ANTISTATIC PERFORMANCES.
 3. THE OUTER SHELL ADOPTS PLASTIC, AND THE COLOR IS BLACK.
 4. LINE 14-6CX-XXX WITH 2x6 HOUSING RECEPTACLES, CABLE LENGTH 500mm, PEEL OFF OUTER INSULATION FOR 150mm LONG AND WRAP SHIELDED PAPER CONNECT TO
 - 6XXX SERIAL CONTROL BOARD
 - 6XXX USB CONTROL BOARD
 5. GLASS THICKNESS: 3mm NOMINAL.
 6. COVERSHEET TYPE: CLEAR.

						Leading Touch DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS TOLERANCES ARE: LINEAR TOL: X=±1.0 .X=±1.0 .XX=±0.5 ANGULAR TOL: ±1°	MODEL TB-1749	PROJECTION
							DESCRIPTION 17" SAW touchbezel	SIZE: A4 SCALE 1:1
							MATERIAL	WEIGHT: 1.03 Kg
							FINISH	COLOR: BLACK
A	FIRST ISSUE	2009-11-21	Sara	DavId	Cloud			
REV.	DESCRIPTION	DATE	DRAW	CHECK	APPROVE	DRAWING NO.:	SHEET 1 OF 1	REV. A