



| CONNECTION CHART | | | |
|------------------|-------------|------------------|--------------|
| PIN | SIGNAL | INSULATION COLOR | JACKET COLOR |
| 1 | GROUND | OVERALL SHIELD | |
| 2 | KEY | | |
| 3 | Y RECEIVE+ | BLU | BLK |
| 4 | Y TRANSMIT+ | BLU | GRY |
| 5 | Y RECEIVE- | BLK | BLK |
| 6 | Y TRANSMIT- | YEL | GRY |
| 7 | GROUND | INNER SHIELD | |
| 8 | X TRANSMIT- | RED | RED |
| 9 | X RECEIVE- | RED | BLK |
| 10 | X TRANSMIT+ | GRN | RED |
| 11 | X RECEIVE+ | WHT | BLK |
| 12 | KEY | | |

NOTES:

- ALL DIMENSIONS ARE IN MILLIMETERS. DIMENTIONS SHOWN ARE PROJECTED DISTANCES.
- GLASS THICKNESS:6mm NOMINAL.
- WATERPROOF, DUSTPROOF, ANTIMAGNETIC, ANTISTATIC AND BREAK RESISTANT PERFORMANCES.
- THE OUTER SHELL ADOPTS SPRAY-PLASTIC OF STAINLESS STEEL , AND THE COLOR IS BLACK.
- LINE 14-6CX-XXX, WITH 2x6 HOUSING RECEPTACLES, CONNECT TO
 -----SAW SERIAL CONTROL BOARD SAW232(6000S)
 -----SAW USB CONTROL BOARD SAWUSB (6000U)

| | | | | | | | | |
|------|--------------|----------|-------|-------|---------|--|-----------------------------------|----------------|
| | | | | | | Leading Touch DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS TOLERANCES ARE: LINEAR TOL: .X=±1.0 .XX=±0.5 ANGULAR TOL: ±1° | MODEL TB-S156LE3 | PROJECTION |
| | | | | | | | DESCRIPTION 15" SAW touchbezel | SIZE: A4 |
| | | | | | | | MATERIAL | WEIGHT: Kg |
| | | | | | | | FINISH | COLOR: |
| B | SECOND ISSUE | 09-12-04 | Sara | David | CLOUD | | | |
| A | FIRST ISSUE | 08-5-14 | Found | BING | CLOUD | | | |
| REV. | DESCRIPTION | DATE | DRAW | CHECK | APPROVE | DRAWING NO.: | SHEET 1 OF 1 | REV. B |