



NOTES:  
 1. ALL DIMENSIONS ARE IN MILLIMETERS. DIMENTIONS SHOWN ARE PROJECTED DISTANCES.  
 2. GLASS THICKNESS:6mm NOMINAL.  
 3. WATERPROOF, DUSTPROOF, ANTIMAGNETIC, ANTISTATIC AND BREAK RESISTANT PERFORMANCES.  
 4. THE OUTER SHELL ADOPTS SPRAY-PLASTIC OF STAINLESS STEEL , AND THE COLOR IS BLACK.  
 5. LINE 14-6CX-XXX,WITH 2x6 HOUSING RECEPTLES, CONNECT TO  
 -----SAW SERIAL CONTROL BOARD SAW232(6000S)  
 -----SAW USB CONTROL BOARD SAWUSB (6000U)

CONNECTION CHART			
PIN	SIGNAL	INSULATION COLOR	JACKET COLOR
1	GROUND	OVERALL SHIELD	
2	KEY		
3	Y RECEIVE+	BLU	BLK
4	Y TRANSMIT+	BLU	GRY
5	Y RECEIVE-	BLK	BLK
6	Y TRANSMIT-	YEL	GRY
7	GROUND	INNER SHIELD	
8	X TRANSMIT-	RED	RED
9	X RECEIVE-	RED	BLK
10	X TRANSMIT+	GRN	RED
11	X RECEIVE+	WHT	BLK
12	KEY		

						<p>DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED          ALL DIMENSIONS ARE IN MILLIMETERS          TOLERANCES ARE:          LINEAR TOL: .X=±1.0          .XX=±0.5          ANGULAR TOL: ±1°</p>	MODEL TB-S176LE1	PROJECTION 
							DESCRIPTION 17" SAW touch bezel	SIZE: A4
							MATERIAL	WEIGHT: Kg
							FINISH	COLOR:
B	SECOND ISSUE	09-12-04	Sara	David	CLOUD			
A	FIRST ISSUE	08-5-14	Found	BING	CLOUD			
REV.	DESCRIPTION	DATE	DRAW	CHECK	APPROVE	DRAWING NO.:	SHEET 1 OF 1	REV. B