



CONNECTION CHART			
PIN	SIGNAL	INSULATION COLOR	JACKET COLOR
1	GROUND	OVERALL SHIELD	
2	KEY		
3	Y RECEIVE+	BLU	BLK
4	Y TRANSMIT+	BLU	GRY
5	Y RECEIVE-	BLK	BLK
6	Y TRANSMIT-	YEL	GRY
7	GROUND	INNER SHIELD	
8	X TRANSMIT-	RED	RED
9	X RECEIVE-	RED	BLK
10	X TRANSMIT+	GRN	RED
11	X RECEIVE+	WHT	BLK
12	KEY		

NOTES:
 1. ALL DIMENSIONS ARE IN MILLIMETERS. DIMENTIONS SHOWN ARE PROJECTED DISTANCES.
 2. GLASS THICKNESS:6mm NOMINAL.
 3. WATERPROOF, DUSTPROOF, ANTIMAGNETIC, ANTISTATIC AND BREAK RESISTANT PERFORMANCES.
 4. THE OUTER SHELL ADOPTS SPRAY-PLASTIC OF STAINLESS STEEL , AND THE COLOR IS BLACK.
 ⑤ LINE 14-6CX-XXX, WITH 2x6 HOUSING RECEPTACLES, CONNECT TO
 -----SAW SERIAL CONTROL BOARD SAW232(6000S)
 -----SAW USB CONTROL BOARD SAWUSB (6000U)

REV.	DESCRIPTION	DATE	DRAW	CHECK	APPROVE	DRAWING NO.:
B	SECOND ISSUE	09-12-04	Sara	David	CLOUD	
A1	FIRST ISSUE	08-5-14	Found	BING	CLOUD	

<p>DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS TOLERANCES ARE: LINEAR TOL: .X=±1.0 .XX=±0.5 ANGULAR TOL: ±1°</p>	MODEL	TB-S176ME1	PROJECTION	
	DESCRIPTION	17" SAW touch bezel	SIZE:	A4
	MATERIAL		WEIGHT:	Kg
	FINISH		COLOR:	
SHEET 1 OF 1		REV. B		