



CONNECTION CHART			
PIN	SIGNAL	INSULATION COLOR	JACKET COLOR
1	GROUND	OVERALL SHIELD	
2	KEY		
3	Y RECEIVE+	BLU	BLK
4	Y TRANSMIT+	BLU	GRY
5	Y RECEIVE-	BLK	BLK
6	Y TRANSMIT-	YEL	GRY
7	GROUND	INNER SHIELD	
8	X TRANSMIT-	RED	RED
9	X RECEIVE-	RED	BLK
10	X TRANSMIT+	GRN	RED
11	X RECEIVE+	WHT	BLK
12	KEY		

**NOTES:**

- ALL DIMENSIONS ARE IN MILLIMETERS. DIMENTIONS SHOWN ARE PROJECTED DISTANCES.
- GLASS THICKNESS:6mm NOMINAL.
- WATERPROOF, DUSTPROOF, ANTIMAGNETIC, ANTISTATIC AND BREAK RESISTANT PERFORMANCES.
- THE OUTER SHELL ADOPTS SPRAY-PLASTIC OF STAINLESS STEEL , AND THE COLOR IS BLACK.
- LINE 14-6CX-XXX, WITH 2x6 HOUSING RECEPTACLES, CONNECT TO  
 -----SAW SERIAL CONTROL BOARD SAW232(6000S)  
 -----SAW USB CONTROL BOARD SAWUSB (6000U)

						<b>Leading Touch</b> DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS TOLERANCES ARE: LINEAR TOL: X=±1.0 .XX=±0.5 ANGULAR TOL: ±1°	MODEL TB-S196LE3	PROJECTION 
							DESCRIPTION 19" SAW touchbezel	SIZE: A4
							MATERIAL	WEIGHT: Kg
							FINISH	COLOR:
B	SECOND ISSUE	09-12-04	Sara	David	CLOUD			
A1	FIRST ISSUE	08-5-14	Found	BING	CLOUD			
REV.	DESCRIPTION	DATE	DRAW	CHECK	APPROVE	DRAWING NO.:	SHEET 1 OF 1	REV. B