



Number	Signal name
1	+5V
2	D-
3	D+
4	GND

P/N	DESCRIPTION	GLASS TYPE	DEPTH DETAILS	NET WEIGHT
IRM1501U1-G31	15" single-touch infrared touchscreen	3mm tempered clear glass	10mm	TBD
IRM1501U1-N31		3mm tempered anti-glare glass		
IRM1501U1-A31		3mm tempered anti-reflective glass		
IRM1501U8-G31	15" multi-touch infrared touchscreen	3mm tempered clear glass	10mm	TBD
IRM1501U8-N31		3mm tempered anti-glare glass		
IRM1501U8-A31		3mm tempered anti-reflective glass		

NOTE:
 1. IRM1501U1 SERIES: SINGLE-TOUCH MODE;
 IRM1501U8 SERIES: MULTI-TOUCH MODE.
 2. PANEL TAIL CONNECTOR:USB MALE.
 3. FRAME MATERIAL IS METAL.THE FRAME IS HIGHER THAN THE GLASS SURFACE FOR 4.5MM.
 4. ALL DIMENSIONS ARE IN MILLIMETERS.

						Leading Touch DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS TOLERANCES ARE: LINEAR TOL: .X=±1.0 .XX=±0.5 ANGULAR TOL: ±1°	MODEL IRM1501U	PROJECTION
							DESCRIPTION 15" Infrared Touchscreen USB Interface	SIZE: A4 NO SCALE
							ASPECT RATIO 4:3	COLOR: BLACK
A	FIRST ISSUE	11-10-09	Rong	Jocelyn	Cloud			
REV.	DESCRIPTION	DATE	DRAW	CHECK	APPROVE	DRAWING NO.:	SHEET 1 OF 1	REV. A