



Detail A  
6:1

Number	Signal name
1	+5V
2	D-
3	D+
4	GND

P/N	DESCRIPTION	GLASS TYPE	DEPTH DETAILS	NET WEIGHT
IRS2201U1-G00	22" single-touch infrared touchscreen	no glass	9mm	0.3kg
IRS2201U1-G41		4mm tempered clear glass	13.5mm	2kg
IRS2201U1-N41		4mm tempered anti-glare glass		
IRS2201U1-A41		4mm tempered anti-reflective glass		
IRS2201U8-G00	22" multi-touch infrared touchscreen	no glass	9mm	0.3kg
IRS2201U8-G41		4mm tempered clear glass	13.5mm	2kg
IRS2201U8-N41		4mm tempered anti-glare glass		
IRS2201U8-A41		4mm tempered anti-reflective glass		

- NOTE:
- IRS2201U1 SERIES: SINGLE-TOUCH MODE;  
IRS2201U8 SERIES: MULTI-TOUCH MODE.
  - PANEL TAIL CONNECTOR:USB MALE.
  - FRAME MATERIAL IS ALUMINUM ALLOY.
  - DEPTH:SEE DETAILS IN RIGHT TABLE FOR VARIOUS P/N.
  - ALL DIMENSIONS ARE IN MILLIMETERS.

						<b>Leading Touch</b>	MODEL IRS2201U	PROJECTION 
							DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS TOLERANCES ARE: LINEAR TOL: .X=±1.0 .XX=±0.5 ANGULAR TOL: ±1°	DESCRIPTION 22" Infrared Touchscreen USB Interface
A	FIRST ISSUE	11-01-12	Fang	Jocelyn	Cloud	DRAWING NO.:		SHEET 1 OF 1
REV.	DESCRIPTION	DATE	DRAW	CHECK	APPROVE			REV. A