


Detail A-A  
6:1



Number	Signal name
1	+5V
2	D-
3	D+
4	GND

P/N	DESCRIPTION	GLASS TYPE	DEPTH DETAILS	NET WEIGHT
IRS6001U1-G00	60" single-touch infrared touchscreen	no glass	12.8mm	1.1kg
IRS6001U1-G41		4mm tempered clear glass	17mm	TBD
IRS6001U1-N41		4mm tempered anti-glare glass		
IRS6001U1-A41		4mm tempered anti-reflective glass		
IRS6001U8-G00	60" multi-touch infrared touchscreen	no glass	12.8mm	1.1kg
IRS6001U8-G41		4mm tempered clear glass	17mm	TBD
IRS6001U8-N41		4mm tempered anti-glare glass		
IRS6001U8-A41		4mm tempered anti-reflective glass		

**Leading Touch**


DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED  
ALL DIMENSIONS ARE IN MILLIMETERS  
TOLERANCES ARE:  
LINEAR TOL: .XX=±1.0  
.XX=±0.5  
ANGULAR TOL: ±1°

MODEL IRS6001U	PROJECTION 
DESCRIPTION 60" Infrared Touchscreen USB Interface	SIZE: A4 NO SCALE
ASPECT RATIO 16:9	COLOR: BLACK

REV.	DESCRIPTION	DATE	DRAW	CHECK	APPROVE	DRAWING NO.:
A	FIRST ISSUE	11-09-20	Rong	Jocelyn	Cloud	

- NOTE:
- IRS6001U1 SERIES: SINGLE-TOUCH MODE;  
IRS6001U8 SERIES: MULTI-TOUCH MODE.
  - PANEL TAIL CONNECTOR:USB MALE.
  - FRAME MATERIAL IS ALUMINUM ALLOY.
  - DEPTH:SEE DETAILS IN RIGHT TABLE FOR VARIOUS P/N.
  - ALL DIMENSIONS ARE IN MILLIMETERS.

AC Adapter power cable  
14-612-200, length 2000mm



L=300mm  
L=1500mm