



P/N	SURFACE FINISH	GLASS THICKNESS
SA0700D30-G4	CLEAR	4
SA0700D30-N4	ANTI-GLARE	4
SA0700D30-A4	ANTI-REFLECTIVE	4

- NOTES:
- ALL DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS SHOWN ARE PROJECTED DISTANCES.
  - THE GLASS THICKNESS:4mm NOMINAL.
  - DUSTPROOF, ANTIMAGNETIC, ANTISTATIC PERFORMANCES.
  - THE OUTER SHELL ADOPTS SPRAY-PLASTIC OF ALUMINUM EXTRUSION PROFILES, AND THE COLOR IS BLACK.
- ⑤ LINE 14-6CX-XXX, WITH 2x6 HOUSING RECEPTACLES, CONNECT TO
- COMBO SERIAL RS232 AND USB SAW CONTROLLER
  - USB SAW CONTROLLER
  - SERIAL RS232 SAW CONTROLLER

CONNECTION CHART			
PIN	SIGNAL	INSULATION COLOR	JACKET COLOR
1	GROUND	OVERALL SHIELD	
2	KEY		
3	Y RECEIVE+	BLU	BLK
4	Y TRANSMIT+	BLU	GRY
5	Y RECEIVE-	BLK	BLK
6	Y TRANSMIT-	YEL	GRY
7	GROUND	INNER SHIELD	
8	X TRANSMIT-	RED	RED
9	X RECEIVE-	RED	BLK
10	X TRANSMIT+	GRN	RED
11	X RECEIVE+	WHT	BLK
12	KEY		

					<p><b>Leading Touch</b></p> <p>DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED</p> <p>ALL DIMENSIONS ARE IN MILLIMETERS</p> <p>TOLERANCES ARE:            LINEAR TOL: .X=±1.0            .XX=±0.5            ANGULAR TOL: ±1°</p>	MODEL	PROJECTION
						SA0700D30-G4	
						DESCRIPTION	SIZE: A4
						7" Wide Protected-Dust Panel	SCALE 1:1
					MATERIAL	WEIGHT:	
						Kg	
					FINISH	COLOR:	
A	FIRST ISSUE	08-9-23	Found	BING	CLOUD		
REV.	DESCRIPTION	DATE	DRAW	CHECK	APPROVE	DRAWING NO.:	