



P/N	SURFACE FINISH	GLASS THICKNESS
SA1021P30-G6	CLEAR	6
SA1021P30-N6	ANTI-GLARE	6
SA1021P30-A6	ANTI-REFLECTIVE	6

CONNECTION CHART			
PIN	SIGNAL	INSULATION COLOR	JACKET COLOR
1	GROUND	OVERALL SHIELD	
2	KEY		
3	Y RECEIVE+	BLU	BLK
4	Y TRANSMIT+	BLU	GRY
5	Y RECEIVE-	BLK	BLK
6	Y TRANSMIT-	YEL	GRY
7	GROUND	INNER SHIELD	
8	X TRANSMIT-	RED	RED
9	X RECEIVE-	RED	BLK
10	X TRANSMIT+	GRN	RED
11	X RECEIVE+	WHT	BLK
12	KEY		

- NOTES:  
 1. ALL DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS SHOWN ARE PROJECTED DISTANCES.  
 2. GLASS THICKNESS:6mm, HEAT STRENGTHENED,MEET UL-60950 STEEL BALL DROP TEST.  
 3. IP65 WATERPROOF, DUSTPROOF, ANTIMAGNETIC, ANTISTATIC AND BREAK RESISTANT PERFORMANCES.  
 4. THE OUTER SHELL MATERIAL: ALUMINUM ALLOY,SPRAY-PLASTIC BLACK  
 5. LINE 14-6CX-XXX,WITH 2x6 HOUSING RECEPTACLES, CONNECT TO  
 -----COMBO SERIAL RS232 AND USB SAW CONTROLLER  
 -----USB SAW CONTROLLER  
 -----SERIAL RS232 SAW CONTROLLER

							MODEL SA1021P30-G6	PROJECTION 
							DESCRIPTION 10.2" Wide IP level SAW Touch Panel	SIZE: A4 SCALE 1:1 WEIGHT: COLOR: Black
						DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS TOLERANCES ARE: LINEAR TOL: .X=±1.0 .XX=±0.5 ANGULAR TOL: ±1°		
A	FIRST ISSUE	11-09-14	Jocelyn	Bing	Cloud			
REV.	DESCRIPTION	DATE	DRAW	CHECK	APPROVE	DRAWING NO.:	SHEET 1 OF 1	REV. A