



P/N	SURFACE FINISH	GLASS THICKNESS
SA1021W30-G4	CLEAR	4
SA1021W30-N4	ANTI-GLARE	4
SA1021W30-A4	ANTI-REFLECTIVE	4

- NOTES:
- ALL DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS SHOWN ARE PROJECTED DISTANCES.
 - THE GLASS THICKNESS: 4mm NOMINAL.
 - WATERPROOF, DUSTPROOF, ANTIMAGNETIC, ANTISTATIC PERFORMANCES.
 - THE OUTER SHELL ADOPTS SPRAY-PLASTIC OF ALUMINUM EXTRUSION PROFILES, AND THE COLOR IS BLACK.
- ⑤ LINE 14-6CX-XXX, WITH 2x6 HOUSING RECEPTACLES, CONNECT TO
- COMBO SERIAL RS232 AND USB SAW CONTROLLER
 - USB SAW CONTROLLER
 - SERIAL RS232 SAW CONTROLLER



CONNECTION CHART			
PIN	SIGNAL	INSULATION COLOR	JACKET COLOR
1	GROUND	OVERALL SHIELD	
2	KEY		
3	Y RECEIVE+	BLU	BLK
4	Y TRANSMIT+	BLU	GRY
5	Y RECEIVE-	BLK	BLK
6	Y TRANSMIT-	YEL	GRY
7	GROUND	INNER SHIELD	
8	X TRANSMIT-	RED	RED
9	X RECEIVE-	RED	BLK
10	X TRANSMIT+	GRN	RED
11	X RECEIVE+	WHT	BLK
12	KEY		

REV.	DESCRIPTION	DATE	DRAW	CHECK	APPROVE
A	FIRST ISSUE	11-07-25	Fang	Jocelyn	Cloud

Leading Touch

DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED
 ALL DIMENSIONS ARE IN MILLIMETERS
 TOLERANCES ARE:
 LINEAR TOL: .XX=±1.0
 .XX=±0.5
 ANGULAR TOL: ±1°

MODEL SA1021W30-G4	PROJECTION
DESCRIPTION 10.2" Wide Protected-Water Panel	SIZE: A4
	SCALE 1:1
	COLOR: Black
DRAWING NO.:	
SHEET 1 OF 1	
REV. A	