



P/N	SURFACE FINISH	GLASS THICKNESS
SA1211P30-G6	CLEAR	6
SA1211P30-N6	ANTI-GLARE	6
SA1211P30-A6	ANTI-REFLECTIVE	6

CONNECTION CHART			
PIN	SIGNAL	INSULATION COLOR	JACKET COLOR
1	GROUND	OVERALL SHIELD	
2	KEY		
3	Y RECEIVE+	BLU	BLK
4	Y TRANSMIT+	BLU	GRY
5	Y RECEIVE-	BLK	BLK
6	Y TRANSMIT-	YEL	GRY
7	GROUND	INNER SHIELD	
8	X TRANSMIT-	RED	RED
9	X RECEIVE-	RED	BLK
10	X TRANSMIT+	GRN	RED
11	X RECEIVE+	WHT	BLK
12	KEY		

- NOTES:
- ALL DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS SHOWN ARE PROJECTED DISTANCES.
 - GLASS THICKNESS:6mm, HEAT STRENGTHENED,MEET UL-60950 STEEL BALL DROP TEST.
 - IP65 WATERPROOF, DUSTPROOF, ANTIMAGNETIC, ANTISTATIC AND BREAK RESISTANT PERFORMANCES.
 - THE OUTER SHELL MATERIAL: ALUMINUM ALLOY,SPRAY-PLASTIC BLACK
 - LINE 14-6CX-XXX WITH 2x6 HOUSING RECEPTACLES, CONNECT TO
 - COMBO SERIAL RS232 AND USB SAW CONTROLLER
 - USB SAW CONTROLLER
 - SERIAL RS232 SAW CONTROLLER

					<p>DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS TOLERANCES ARE: LINEAR TOL: X=±1.0 .XX=±0.5 ANGULAR TOL: ±1°</p>	MODEL	PROJECTION
						SA1211P30-G6	
						DESCRIPTION	SIZE: A4
						12"W IP level SAW touchscreen	SCALE 1:1
					MATERIAL	WEIGHT:	
						Kg	
					FINISH	COLOR:	
A	FIRST ISSUE	10-4-1	Sara	David	CLOUD		
REV.	DESCRIPTION	DATE	DRAW	CHECK	APPROVE	DRAWING NO.:	SHEET 1 OF 1
							REV. A