CONNECTION CHART			
PIN	SIGNAL	INSULATION COLOR	JACKET COLOR
1	GROUND	OVERALL SHIELD	
2	KEY		
3	Y RECEIVE+	BLU	BLK
4	Y TRANSMIT+	BLU	GRY
5	Y RECEIVE−	BLK	BLK
6	Y TRANSMIT−	YEL	GRY
7	GROUND	INNER SHIELD	
8	X TRANSMIT−	RED	RED
9	X RECEIVE−	RED	BLK
10	X TRANSMIT+	GRN	RED
11	X RECEIVE+	WHT	BLK
12	KEY		

P/N	SURFACE FINISH	GLASS THICKNESS
SA1560D30-G4	CLEAR	4
SA1560D30-N4	ANTI-GLARE	4
SA1560D30-A4	ANTI-REFLECTIVE	4

NOTES:
1. ALL DIMENSIONS ARE IN MILLMETERS. DIMENTIONS SHOWN ARE PROJECTED DISTANCES.
2. THE GLASS THICKNESS:4mm NOMINAL.
3. DUSTPROOF, ANTIMAGNETIC,ANTISTATIC PERFORMANCES.
4. THE OUTER SHELL ADOPTS SPRAY-PLASTIC OF ALUMINUM EXTRUSION PROFILES , AND THE COLOR IS BLACK.
5. LINE 14-6CX-XXX,WITH 2x6 HOUSING RECEPTACLES, CONNECT TO
   -----COMBO SERIAL RS232 AND USB SAW CONTROLLER
   -----USB SAW CONTROLLER
   -----SERIAL RS232 SAW CONTROLLER

REV.	DESCRIPTION	DATE	DRAW	CHECK	APPROVE
A	FIRST ISSUE	09-11-17	Sara	David	CLOUD

Leading Touch

DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE IN MILLIMETERS
TOLERANCES ARE:
LINEAR TOL: .X=±1.0
.XX=±0.5
ANGULAR TOL: ±1°

MODEL: SA1560D30-G4	PROJECTION
DESCRIPTION: 15" Wide Protected-Dust Panel	SIZE: A4
MATERIAL	SCALE 1:1
FINISH	WEIGHT: Kg
	COLOR:
DRAWING NO.:	SHEET 1 OF 1 / REV. A