


P/N	SURFACE FINISH	GLASS THICKNESS
SA1711D30-G4	CLEAR	4
SA1711D30-N4	ANTI-GLARE	4
SA1711D30-A4	ANTI-REFLECTIVE	4

- NOTES:
- ALL DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS SHOWN ARE PROJECTED DISTANCES.
 - THE GLASS THICKNESS:4mm NOMINAL.
 - DUSTPROOF, ANTIMAGNETIC, ANTISTATIC PERFORMANCES.
 - THE OUTER SHELL ADOPTS SPRAY-PLASTIC OF ALUMINUM EXTRUSION PROFILES, AND THE COLOR IS BLACK.
- ⑤ LINE 14-6CX-XXX, WITH 2x6 HOUSING RECEPTACLES, CONNECT TO
- COMBO SERIAL RS232 AND USB SAW CONTROLLER
 - USB SAW CONTROLLER
 - SERIAL RS232 SAW CONTROLLER



CONNECTION CHART			
PIN	SIGNAL	INSULATION COLOR	JACKET COLOR
1	GROUND	OVERALL SHIELD	
2	KEY		
3	Y RECEIVE+	BLU	BLK
4	Y TRANSMIT+	BLU	GRY
5	Y RECEIVE-	BLK	BLK
6	Y TRANSMIT-	YEL	GRY
7	GROUND	INNER SHIELD	
8	X TRANSMIT-	RED	RED
9	X RECEIVE-	RED	BLK
10	X TRANSMIT+	GRN	RED
11	X RECEIVE+	WHT	BLK
12	KEY		

						<p>Leading Touch</p> <p>DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED</p> <p>ALL DIMENSIONS ARE IN MILLIMETERS</p> <p>TOLERANCES ARE: LINEAR TOL: .X=±1.0 .XX=±0.5 ANGULAR TOL: ±1°</p>	MODEL SA1711D30-G4	PROJECTION
							DESCRIPTION 17" Wide Protected-Dust Panel	SIZE: A4
							MATERIAL	WEIGHT: Kg
							FINISH	COLOR:
A	FIRST ISSUE	08-9-23	Found	BING	CLOUD	DRAWING NO.:		SHEET 1 OF 1
REV.	DESCRIPTION	DATE	DRAW	CHECK	APPROVE			REV. A