





P/N	SURFACE FINISH	GLASS THICKNESS
SA1910P10-G6	CLEAR	6
SA1910P10-N6	ANTI-GLARE	6

CONNECTION CHART			
PIN	SIGNAL	INSULATION COLOR	JACKET COLOR
1	GROUND	OVERALL SHIELD	
2	KEY		
3	Y RECEIVE+	BLU	BLK
4	Y TRANSMIT+	BLU	GRY
5	Y RECEIVE−	BLK	BLK
6	Y TRANSMIT−	YEL	GRY
7	GROUND	INNER SHIELD	
8	X TRANSMIT−	RED	RED
9	X RECEIVE−	RED	BLK
10	X TRANSMIT+	GRN	RED
11	X RECEIVE+	WHT	BLK
12	KEY		

NOTES:
1. ALL DIMENSIONS ARE IN MILLMETERS. DIMENTIONS SHOWN ARE PROJECTED DISTANCES.
2. THE HEAT STRENGTHENED GLASS THICKNESS:6mm NOMINAL.
3. WATERPROOF, DUSTPROOF, ANTIMAGNETIC, ANTISTATIC AND BREAK RESISTANT PERFORMANCES.
4. THE OUTER SHELL ADOPTS SPRAY-PLASTIC OF STAINLESS STEEL , AND THE COLOR IS BLACK.
5. LINE 14-6CX-XXX,WITH 2x6 HOUSING RECEPTACLES, CONNECT TO
   -----SAW SERIAL CONTROL BOARD SAW232(6000S)
   -----SAW USB CONTROL BOARD SAWUSB (6000U)

REV.	DESCRIPTION	DATE	DRAW	CHECK	APPROVE
A0	FIRST ISSUE	08-1-29	Found	BING	CLOUD

Leading Touch

DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS ARE IN MILLIMETERS
TOLERANCES ARE:
LINEAR TOL: .X=±1.0
.XX=±0.5
ANGULAR TOL: ±1°

MODEL: SA1910P10-G6	PROJECTION
DESCRIPTION: 19" SAW touchscreen	SIZE: A4
	SCALE 1:1
MATERIAL	WEIGHT: Kg
FINISH	COLOR:
DRAWING NO.:	SHEET 1 OF 1 / REV. A0