


P/N	SURFACE FINISH	GLASS THICKNESS
SA1911P30-G6	CLEAR	6
SA1911P30-N6	ANTI-GLARE	6
SA1911P30-A6	ANTI-REFLECTIVE	6

CONNECTION CHART			
PIN	SIGNAL	INSULATION COLOR	JACKET COLOR
1	GROUND	OVERALL SHIELD	
2	KEY		
3	Y RECEIVE+	BLU	BLK
4	Y TRANSMIT+	BLU	GRY
5	Y RECEIVE-	BLK	BLK
6	Y TRANSMIT-	YEL	GRY
7	GROUND	INNER SHIELD	
8	X TRANSMIT-	RED	RED
9	X RECEIVE-	RED	BLK
10	X TRANSMIT+	GRN	RED
11	X RECEIVE+	WHT	BLK
12	KEY		



- NOTES:
- ALL DIMENSIONS ARE IN MILLIMETERS. DIMENTIONS SHOWN ARE PROJECTED DISTANCES.
 - GLASS THICKNESS:6mm, HEAT STRENGTHENED,MEET UL-60950 STEEL BALL DROP TEST.
 - IP65 WATERPROOF, DUSTPROOF, ANTIMAGNETIC, ANTISTATIC AND BREAK RESISTANT PERFORMANCES.
 - THE OUTER SHELL MATERIAL: ALUMINUM ALLOY,SPRAY-PLASTIC BLACK
 - LINE 14-6CX-XXX,WITH 2x6 HOUSING RECEPTACLES, CONNECT TO
 - COMBO SERIAL RS232 AND USB SAW CONTROLLER
 - USB SAW CONTROLLER
 - SERIAL RS232 SAW CONTROLLER

					Leading Touch		MODEL SA1911P30-G6	PROJECTION
					DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS TOLERANCES ARE: LINEAR TOL: .X=±1.0 .XX=±0.5 ANGULAR TOL: ±1°		DESCRIPTION 19" Wide IP level SAW touchscreen	SIZE: A4
							MATERIAL	WEIGHT: Kg
							FINISH	COLOR:
REV.	DESCRIPTION	DATE	DRAW	CHECK	APPROVE	DRAWING NO.:		SHEET 1 OF 1
A	FIRST ISSUE	08-8-20	Found	BING	CLOUD			REV. A