



P/N	SURFACE FINISH	GLASS THICKNESS
SA2010W30-G4	CLEAR	4
SA2010W30-N4	ANTI-GLARE	4

- NOTES:
- ALL DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS SHOWN ARE PROJECTED DISTANCES.
  - THE GLASS THICKNESS:4mm NOMINAL.
  - WATERPROOF, DUSTPROOF, ANTIMAGNETIC,ANTISTATIC PERFORMANCES.
  - THE OUTER SHELL ADOPTS SPRAY-PLASTIC OF ALUMINUM EXTRUSION PROFILES , AND THE COLOR IS BLACK.
- ⑤ LINE 14-6CX-XXX,WITH 2x6 HOUSING RECEPTACLES, CONNECT TO  
 ----SAW SERIAL CONTROL BOARD SAW232(6000S)  
 ----SAW USB CONTROL BOARD SAWUSB (6000U)

CONNECTION CHART			
PIN	SIGNAL	INSULATION COLOR	JACKET COLOR
1	GROUND	OVERALL SHIELD	
2	KEY		
3	Y RECEIVE+	BLU	BLK
4	Y TRANSMIT+	BLU	GRY
5	Y RECEIVE-	BLK	BLK
6	Y TRANSMIT-	YEL	GRY
7	GROUND	INNER SHIELD	
8	X TRANSMIT-	RED	RED
9	X RECEIVE-	RED	BLK
10	X TRANSMIT+	GRN	RED
11	X RECEIVE+	WHT	BLK
12	KEY		

						<p>DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED          ALL DIMENSIONS ARE IN MILLIMETERS          TOLERANCES ARE:          LINEAR TOL: X=±1.0          .XX=±0.5          ANGULAR TOL: ±1°</p>	MODEL SA2010W30-G4	PROJECTION 
							DESCRIPTION 20.1" Protected-Water Panel	SIZE: A4
							MATERIAL	WEIGHT: Kg
							FINISH	COLOR:
A	FIRST ISSUE	09-10-10	Sara	David	Cloud			
REV.	DESCRIPTION	DATE	DRAW	CHECK	APPROVE	DRAWING NO.:	SHEET 1 OF 1	REV. A