



P/N	COVERSHEET TYPE	GLASS THICKNESS
SA2011S12-G4	CLEAR	
SA2011S12-N4	ANTI-GLARE	4.0mm



CONNECTION CHART			
PIN	SIGNAL	INSULATION COLOR	JACKET COLOR
1	GROUND	OVERALL SHIELD	
2	KEY		
3	Y RECEIVE+	BLU	BLK
4	Y TRANSMIT+	BLU	GRY
5	Y RECEIVE-	BLK	BLK
6	Y TRANSMIT-	YEL	GRY
7	GROUND	INNER SHIELD	
8	X TRANSMIT-	RED	RED
9	X RECEIVE-	RED	BLK
10	X TRANSMIT+	GRN	RED
11	X RECEIVE+	WHT	BLK
12	KEY		

**NOTES:**

- ALL DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS SHOWN ARE PROJECTED DISTANCES.
- GLASS THICKNESS: 4.0±0.3mm NOMINAL.
- TRANSDUCERS ARE LOCATED AT THE POSITIONS SHOWN. HEIGHT OF TRANSDUCERS BELOW GLASS.
- CABLE ROUTING ADDS A MAXIMUM OF 2.5mm AS INDICATED ON THE SCREEN. CABLE IS ROUTED ALONG THE EDGE OF THE GLASS.
- LINE 14-6CX-XXX, WITH 2x6 HOUSING RECEPTACLES, CONNECT TO
  - SAW SERIAL CONTROL BOARD SAW232(6000S)
  - SAW USB CONTROL BOARD SAWUSB (6000U)
- THE TOUCH ACTIVE AREA IS LESS THAN THE VIEWABLE AREA TO FACILITATE SEALING.

REV.	DESCRIPTION	DATE	DRAW	CHECK	APPROVE	DRAWING NO.:	MODEL	PROJECTION
A0	FIRST ISSUE	08-1-29	Found	BING	CLOUD		SA2011S12-G4	
							DESCRIPTION	SIZE: A4
							MATERIAL	SCALE 1:1
							FINISH	WEIGHT: Kg
								COLOR:

**Leading Touch**

DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED  
ALL DIMENSIONS ARE IN MILLIMETERS  
TOLERANCES ARE:  
LINEAR TOL: X=±1.0  
.XX=±0.5  
ANGULAR TOL: ±1°

MODEL	SA2011S12-G4	PROJECTION	
DESCRIPTION	20.1" SAW touchscreen	SIZE:	A4
MATERIAL		SCALE:	1:1
FINISH		WEIGHT:	Kg
		COLOR:	