



P/N	COVERSHEET TYPE	GLASS THICKNESS
SA2130S12-G4	CLEAR	4.0mm
SA2130S12-N4	ANTI-GLARE	

CONNECTION CHART			
PIN	SIGNAL	INSULATION COLOR	JACKET COLOR
1	GROUND	OVERALL SHIELD	
2	KEY		
3	Y RECEIVE+	BLU	BLK
4	Y TRANSMIT+	BLU	GRY
5	Y RECEIVE-	BLK	BLK
6	Y TRANSMIT-	YEL	GRY
7	GROUND	INNER SHIELD	
8	X TRANSMIT-	RED	RED
9	X RECEIVE-	RED	BLK
10	X TRANSMIT+	GRN	RED
11	X RECEIVE+	WHT	BLK
12	KEY		

- NOTES:
- ALL DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS SHOWN ARE PROJECTED DISTANCES.
  - GLASS THICKNESS: 4.0±0.3mm NOMINAL.
  - TRANSDUCERS ARE LOCATED AT THE POSITIONS SHOWN. GLASS IS BEVELED UNDER TRANSDUCERS. HEIGHT OF TRANSDUCERS BELOW GLASS.
  - CABLE ROUTING ADDS A MAXIMUM OF 2.5mm AS INDICATED ON THE SCREEN. CABLE IS ROUTED ALONG THE BEVEL.
  - LINE 14-6CX-XXX, WITH 2x6 HOUSING RECEPTACLES, CONNECT TO  
 -----SAW SERIAL CONTROL BOARD SAW232(6000S)  
 -----SAW USB CONTROL BOARD SAWUSB (6000U)
  - THE TOUCH ACTIVE AREA IS LESS THAN THE VIEWABLE AREA TO FACILITATE SEALING.

					<b>Leading Touch</b> DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN MILLIMETERS TOLERANCES ARE: LINEAR TOL: X=±1.0 .XX=±0.5 ANGULAR TOL: ±1°	MODEL	SA2130S12-G4	PROJECTION	
						DESCRIPTION	21.3" SAW touchscreen	SIZE:	A4
						MATERIAL		WEIGHT:	Kg
						FINISH		COLOR:	
A0	FIRST ISSUE	08-1-29	Found	BING	CLOUD	DRAWING NO.:		SHEET 1 OF 1	REV. A0