



CONNECTION CHART			
PIN	SIGNAL	INSULATION COLOR	JACKET COLOR
1	GROUND	OVERALL SHIELD	
2	KEY		
3	Y RECEIVE+	BLU	BLK
4	Y TRANSMIT+	BLU	GRY
5	Y RECEIVE-	BLK	BLK
6	Y TRANSMIT-	YEL	GRY
7	GROUND	INNER SHIELD	
8	X TRANSMIT-	RED	RED
9	X RECEIVE-	RED	BLK
10	X TRANSMIT+	GRN	RED
11	X RECEIVE+	WHT	BLK
12	KEY		

P/N	SURFACE FINISH	GLASS THICKNESS
SA2150D30-G4	CLEAR	4
SA2150D30-N4	ANTI-GLARE	4
SA2150D30-A4	ANTI-REFLECTIVE	4

- NOTES:
- ALL DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS SHOWN ARE PROJECTED DISTANCES.
  - THE GLASS THICKNESS:4mm NOMINAL.
  - ANTI-VANDAL, DUSTPROOF, ANTIMAGNETIC AND ANTISTATIC PERFORMANCES.
  - THE OUTER SHELL ADOPTS SPRAY-PLASTIC OF ALUMINUM EXTRUSION PROFILES , AND THE COLOR IS BLACK.
- ⑤ LINE 14-6CX-XXX, WITH 2x6 HOUSING RECEPTACLES, CONNECT TO
- COMBO SERIAL RS232 AND USB SAW CONTROLLER
  - USB SAW CONTROLLER
  - SERIAL RS232 SAW CONTROLLER



REV.	DESCRIPTION	DATE	DRAW	CHECK	APPROVE
A	FIRST ISSUE	11-09-05	Jocelyn	XuBing	Cloud

**Leading Touch**

DO NOT SCALE DRAWING UNLESS OTHERWISE SPECIFIED  
ALL DIMENSIONS ARE IN MILLIMETERS  
TOLERANCES ARE:  
LINEAR TOL: .XX=±1.0  
.XX=±0.5  
ANGULAR TOL: ±1°

MODEL <b>SA2150D30-G4</b>	PROJECTION 
DESCRIPTION 21.5" Protected-Dust Panel	SIZE: A4 SCALE 1:1
	WEIGHT: 1.85Kg
	COLOR: BLACK
SHEET 1 OF 1	
REV. A	